

## Vintage Racer Group Tire Rules

*Updated: 1/24/2023*

- Sizing is based on existing rules and regulations for individual car classification.
- Tread must extend across the tire (no DOT slicks with only circumferential grooves).
- Minimum 2/32nds of measurable tread.
- Minimum UTQG of 100 AAA.
- Minimum speed rating of H.

### **Some examples of acceptable tires:**

Avon ACB10, Goodyear Blue Streak, Hoosier Street TD & Speedster, Toyo RA1, R888- R888R, R1R

### **Some examples of non-acceptable tires:**

Slicks or any of the following tires: Avon Tech RA, BFG G -Force R1, Goodyear GS/CS/RS, Hankook Z214, Hoosier DOT Radial, (A6 or R6), Kumho V710, Toyo RR, or any other “street slick” type DOT tire.

### **NON-DOT Racing Tires:**

The non-DOT treaded racing tires listed below are approved for VRG competition:

- Avon: ACB9, CR6ZZ, A29, H-003 and H-009
- Goodyear: BlueStreaks, Vintage Sports Car Specials, G12 and G12A
- Hoosier: Vintage TD, Street TD, Speedster, TDR, TDS, R35B, and VFF
- Dunlop: L series, M-series, CR65, and CR82

Any non-DOT racing tire that is not listed above, is not approved for VRG competition.

### **Contact:**

Specific tire questions may be submitted to the VRG Eligibility Committee:

**[vehicle\\_eligibility@vrgonline.org](mailto:vehicle_eligibility@vrgonline.org)**